

SAVOX

Recon III Probe, Color Camera



The Recon III camera has been completely re-designed to provide unparalleled reliability, durability and ease of use to meet and exceed the operational requirements of a rescue squad or medium/light USAR capability. Building upon the success of the popular Recon II, the Recon III fits today's demanding requirements and more demanding budgets. The new Recon III is affordable, versatile and ready to go!

The Recon III utilizes a 240 degree articulating camera head with variable high output LED lighting to achieve effective visual searching as close as a few inches to over 10 feet (3m) in total darkness. The display is attached to the control housing with a quick connect fitting and can be easily removed to extend the cameras reach. Articulation is accomplished by rotating the large glove friendly drive collar. The pistol grip handle makes positioning and handling intuitive and provides an easy reference for camera head orientation. The lack of external wires and belt packs make the Recon III camera extremely maneuverable and portable.

The Recon III is compatible with batteries and chargers of the SearchCam 3000 and Delsar LD3 and Delsar Mini Systems to aid with logistics on a large scale event. The Recon III is designed for rescue squads that understand the value of an adaptable visual search tool that can be used in a wide variety of operations and want the quality and features found only in a SearchCam product.

Key Benefits

- Each detent represents 15° of camera movement
- 16 high output LED illumination
- Camera head articulates 240° from full left to full right
- Internal self centering clutch mechanism

Savox Communications Oy Ab (Ltd)

Keilaranta 15 B
02150 Espoo, Finland

- Waterproof articulating camera heads
- Lightweight, Lithium-ion batteries
- Drive collar with camera position indicator
- Camera orientation markings
- Pistol grip

Market Segment	Public Safety	Product code	6000-11-014
Size L	1350 mm	Size W	410 mm
Size H	150 mm	Weight (text)	3.4 kg
Storage Temperature Min	-23 °C (-9 °F)	Storage Temperature Max	60 °C (140 °F)
Visual Search Sensor	Yes	Battery Type	XTRACharge
Delivered In a Heavy-duty Case	Yes	Camera Type	Color
Illumination	16 white high output LED with 2 brightness levels	Video Display	ClearSearch Transflective display
Camera Head Articulation	240 °	Camera Head Total Field of Vision	280 °
Reach of the Telescopic Tube Set	1.435 m		